

| Nominal Length | Color Temp. | Input Voltage | Power Consumption | Power Factor | Input Current | Lumens | CRI | Efficacy | Beam Angle | Light Spread |
|----------------|-------------|---------------|-------------------|--------------|------------------------------|--------|-----|----------|------------|--------------|
| 2' | 3000K | 120-277Vac | 7W | >0.9 | 0.06A @ 120V 0.03A @ 277V | 850 | >83 | 121 lm/W | 240° | 325° |
| 2' | 3500K | 120-277Vac | 7W | >0.9 | 0.06A @ 120V 0.03A @ 277V | 850 | >83 | 121 lm/W | 240° | 325° |
| 2' | 4000K | 120-277Vac | 7W | >0.9 | 0.06A @ 120V 0.03A @ 277V | 900 | >83 | 129 lm/W | 240° | 325° |
| 2' | 5000K | 120-277Vac | 7W | >0.9 | 0.06A @ 120V 0.03A @ 277V | 950 | >83 | 136 lm/W | 240° | 325° |
| 2' | 6500K | 120-277Vac | 7W | >0.9 | 0.06A @ 120V 0.03A @ 277V | 950 | >83 | 136 lm/W | 240° | 325° |
| 3' | 3500K | 120-277Vac | 12W | >0.9 | 0.10A @ 120V 0.04A @ 277V | 1,350 | >83 | 113 lm/W | 240° | 325° |
| 3' | 4000K | 120-277Vac | 12W | >0.9 | 0.10A @ 120V 0.04A @ 277V | 1,400 | >83 | 117 lm/W | 240° | 325° |
| 3' | 5000K | 120-277Vac | 12W | >0.9 | 0.10A @ 120V 0.04A @ 277V | 1,450 | >83 | 121 lm/W | 240° | 325° |
| 4' | 3000K | 120-277Vac | 10.5W | >0.9 | 0.09A @ 120V 0.04A @ 277V | 1,650 | >83 | 157 lm/W | 240° | 325° |
| 4' | 3500K | 120-277Vac | 10.5W | >0.9 | 0.09A @ 120V 0.04A @ 277V | 1,650 | >83 | 157 lm/W | 240° | 325° |
| 4' | 4000K | 120-277Vac | 10.5W | >0.9 | 0.09A @ 120V 0.04A @ 277V | 1,700 | >83 | 162 lm/W | 240° | 325° |
| 4' | 5000K | 120-277Vac | 10.5W | >0.9 | 0.09A @ 120V 0.04A @ 277V | 1,720 | >83 | 164 lm/W | 240° | 325° |

**Specifications subject to change without notice