

C N TEXTURED STREETLAMP GLOBES

822 Acorn Globe Series


MATERIALS

- Polycarbonate UV stabilized with continuous operating temperature of 100°C to 125°C and high impact resistance down to -40°C, transmittance of 88% (application dependent). Polycarbonate streetlamps are available in clear.
- Acrylic Impact modified and UV resistant with continuous operating temperature up to 80°C. Maximum transmittance of 92% (clear). Acrylic streetlamps are available in clear.
- LD Acrylic Impact modified and UV resistant with continuous operating temperature up to 80°C and transmittance of 90% to 94% (application dependent). Minimum order quantities apply.
- Polyethylene Impact resistant and offers an affordable cost solution for light housings. Polyethylene streetlamps are available in white.



NECKLESS (N)





ITEM NO.	HEIGHT	WIDTH	ID (NECK)	OD (NECK)	MATERIAL	COLOR
LENS-8229A	16.14"	10.75"	5.25"	N/A	Acrylic	Clear
LENS-8226	16.14"	10.75"	5.25"	N/A	LD Acrylic	Frost
LENS-8229	16.14"	10.75"	5.25"	N/A	Polycarbonate	Clear
LENS-8221PT	16.14"	10.75"	5.25"	N/A	Polyethylene	White

Dimensions are nominal

OPTIONAL ACCESSORIES



MATERIALS

• Polycarbonate - UV stabilized with continuous operating temperature of 100°C to 125°C and high impact resistance down to -40°C. Polycarbonate finials are available in black.

ITEM NO.	HEIGHT	OD (BOTTOM)	MATERIAL	COLOR
99-FINIAL-BLK	5.00"	3.25"	Polycarbonate	Black

Dimensions are nominal